# RESERVE by SOUNDSTREAM.

## DEM UPGRADE HEAD UNIT FOR '98-'13 HARLEY-DAVIDSON® MOTORCYCLES

# INSTALLATION GUIDE











To print a complete owners manual, visit us online at motorcycleaudio.com/hdhu9813RG



scan this QR code with your phone's camera to download the complete owners manual to your phone.



#### Removal of the Original Head Unit

To prevent accidental vehicle start-up, which could cause death or serious injury, remove main fuse before proceeding.

1. Remove each turn indicator by removing 2 bolts for each between the forks/handlebar & inner fairing wall. Use a 1/2" open-end/box-end wrench, ratcheting wrench, or short 1/2" socket and ratchet. The bolt might not unthread from the turn signal housing, however the acorn nut might instead. It will be easier to reinstall the indicator later if the bolt remains on the indicator housing. Set the bolts &/or acorn nuts aside and tuck the indicators aside.



*Tip: Turn the handlebar/front wheel in the direction of the turn indicator you're working on to increase the work area, hopefully preventing bloody knuckles & scratched paint!* 

2. Remove six inner fairing bolts using a T25 Torx screw driver. Two screws are adjacent to the fuel & battery voltage gauges. Two more are located at the outside corner of each speaker grill. The last two screws are below each storage compartment hinge. Store these screws in the storage compartments for re-installation later.

Tip: Note the length of each screw set at the top, mid-section, and lower section as the lengths may differ.

3. While straddling the front wheel fender, grasp the outer fairing & gently pull it away from the inner fairing. With the fairing slightly pulled away from the bike, disconnect wire harness for the headlamp(s) and any other accessories. Lay the fairing on a protected flat surface to prevent damage.

4. Disconnect all wire harnesses from the OEM radio. Use a pry tool, flat-head screwdriver, or pick tool to lift up on the locking tab, then pull the male connector out from the female connector. Also, unplug the FM antenna & disconnect the CB antenna (if equipped). If the OEM SiriusXM tuner is installed, disconnect & remove its antenna, it will not be used.

5. Remove the OEM head unit by removing 4 screws from the head unit support bracket. Use a 3/16" hex/allen key tool to remove 2 screws from each side. Set these four screws aside for reinstallation.









6. Gently pull the OEM radio out and up, away from the support bracket. No other parts from the OEM radio are needed.

7. Take a moment to clean the surfaces of the inner fairing surrounding the cutout for the radio & around the ovalized recess using a damp micro-fiber cloth. Any debris or residue left on these surfaces can affect the water-tight seal around HDHU.9813RG.

### Installation of HDHU.9813RG Head Unit

1. Route the USB cable, antenna extension, & RCA camera input w/ trigger into the cutout of the inner faring. Pull the chassis of the HDHU.9813RG thru the ovalized recess, aligning the mounting screw holes with the holes of the head unit support bracket.


2. Secure HDHU.9813RG to the radio support bracket with the 4 screws set aside during removal of the original head unit (step 5) using the same hex/allan key tool.

3. Insert and lock the male OEM head unit wire harness connector to the female socket of the included wire harness. Then, insert and lock the male connector of the included wire harness into the corresponding female socket on the back of HDHU.9813RG. Swivel the latch into place, locking the male connector into the female receptacle.



4. Empty the contents of the storage compartment you wish to have the USB connector in. Drill a 1" hole in the middle/center of the storage compartment & liner using a 1" spade bit or step bit. Route the USB cable to the back of the storage compartment & into it. Firmly press the rubber grommet into place.

5. Connect the FM radio antenna to the female receptacle extension, and any accessory added to this installation: SiriusXM tuner, Bluetooth calling microphone, camera video-in & trigger, amplifier audio RCA's etc. The wire harness of HDHU.9813RG also includes a blue remote turn-on wire for amplifier(s).



6. Take a moment to reinstall the main fuse if it was removed. At this point, HDHU.9813RG should turnon. Verify all speakers are playing and the head unit is functioning. If successful, tie any loose wires that might impede reinstallation of the fairing.

7. Reassemble the outter fairing to the inner fairing by following the disassembly steps in reverse: Connect headlight wire harnesses & close the fairings together Reattach outter fairing to inner fairing using the six screws removed previously Tuck turn indicator wiring inside the fairing, rettach the turn indicator acorn nuts/bolts

#### LIMITED 90-DAY CONSUMER WARRANTY

# LIMITED TWO-YEAR CONSUMER WARRANTY WITH PURCHASE AND INSTALLATION BY A SOUNDSTREAM OR PRECISIONPOWER AUTHORIZED SELLER

Soundstream promises to the original purchaser, to repair or replace this product with a new or refurbished unit (at Soundstream's sole and absolute discretion) should it prove to be defective in workmanship or material under normal use, for a period of \*two-years from the date of purchase from the Soundstream or PrecisionPower authorized seller, PROVIDED the product was purchased and installed by a Soundstream or PrecisionPower authorized seller. During this \*two-year period, there will be no charge for product repair or replacement, PROVIDED the unit is returned to Soundstream, return shipping pre-paid, along with the required proof of installation, the bill of sale or other dated proof of purchase, and the consumer's contact information.

If the unit is installed by anyone other than a Soundstream or PrecisionPower authorized seller, the warranty period will be 90-days from the date of purchase. This warranty is non-transferable and does not apply to any unit that has been modified or used in a manner contrary to its intended purpose, and does not cover damage to the unit caused by installation or removal of the unit. During this 90-day period, there will be no charge for the repair or replacement PROVIDED the unit is returned to Soundstream, return shipping prepaid, along with the bill of sale or other dated proof of purchase and the consumer's contact information.

This warranty is void if the product has been damaged by accident or unreasonable use, neglect, improper service or other causes not arising out of defects in materials or construction. This warranty does not cover the elimination of externally generated static or noise, or the correction of antenna problems or weak reception, damage to speakers, accessories, electrical systems, cosmetic damage or damage due to negligence, misuse, failure to follow operating instructions, accidental spills or customer applied cleaners, damage due to environmental causes such as floods, airborne fallout, chemicals, salt, hail, lightning or extreme temperatures, damage due to accidents, road hazards, fire, theft, loss or vandalism, damage due to improper connection to equipment of another manufacturer, modification of existing equipment, or Product which has been opened or tampered for any reason. Units which are found to be damaged by abuse resulting in thermally damaged voice coils are not covered by this warranty but may be replaced at the absolute and sole discretion of Soundstream. Unit must be returned to Soundstream, postage pre-paid, with bill of sale or other dated proof of purchase bearing the following information: consumer's name, telephone number, and address, authorized dealer's name and address, and product description. Please contact Soundstream warranty office at 800-724-1377 or repairs@soundstream.com to obtain a Return Authorization number prior to shipping the product.

Note: This warranty does not cover labor costs for the removal and reinstallation of the unit. IN ORDER FOR THE TWO-YEAR WARRANTY TO BE VALID, YOUR UNIT MUST BE SHIPPED WITH PROOF OF INSTALLATION BY A SOUNDSTREAM OR PRECISIONPOWER AUTHORIZED SELLER. ALL UNITS RECEIVED BY SOUNDSTREAM FOR WARRANTY REPAIR WITHOUT PROOF OF SOUNDSTREAM OR PRECISIONPOWER AUTHORIZED DEALER INSTALLATION AND PURCHASE WILL BE COVERED BY THE LIMITED 90-DAY WARRANTY.

BY PURCHASING THIS PRODUCT, ALL WARRANTIES INCLUDING BUT NOT LIMITED TO EXPRESS WARRANTY, IMPLIED WARRANTY, WARRANTY OF MERCHANTABILITY, FITNESS FOR PARTICULAR PURPOSE, AND WARRANTY OF NON-INFRINGEMENT OF INTELLECTUAL PROPERTY ARE EXPRESSLY EXCLUDED TO THE MAXIMUM EXTENT ALLOWED BY LAW, AND SOUNDSTREAM NEITHER ASSUMES NOR AUTHORIZES ANY PERSON TO ASSUME FOR IT ANY LIABILITY IN CONNECTION WITH THE SALE OF THE PRODUCT. SOUNDSTREAM HAS ABSOLUTELY NO LIABILITY FOR ANY AND ALL ACTS OF THIRD PARTIES INCLUDING ITS AUTHORIZED DEALERS OR INSTALLERS. BY PURCHASING THIS PRODUCT, THE CONSUMER AGREES AND CONSENTS THAT ALL DISPUTES BETWEEN THE CONSUMERAND SOUNDSTREAM SHALL BE RESOLVED IN ACCORDANCE WITH CALIFORNIA LAWS IN LOS ANGELES COUNTY, CALIFORNIA. Some states do not allow limitation on how long an implied warranty lasts. In such states, the limitation or exclusions of this Limited Warranty may not apply. Some states do not allow the exclusion or limitation or incidental or consequential damages. In such states, the exclusion or limitation of this Limited Warranty gives you specific legal rights, and you may have other rights which vary from state to state.